



VBS 750 Ultra high temperature vacuum bag sealant tape for use at temperatures to 400°C

Tygavac Sealant VBS 750 has been developed especially for use on high temperature cures. It can be used at temperatures to 400°C and at pressures up to 21 bar.

Most high temperature bagging materials can be sealed effectively using this product. In particular, we would recommend its use with our high temperature bagging films, **Tygavac PBF 400**.

Important Note

An effective seal cannot be achieved when using this sealant in oxygen rich atmosphere. The equipment should be purged with nitrogen during the cure cycle.

Typical Properties

Maximum operating temperature	400°C
Maximum operating pressure	21 bar
Solids content	100%
Colour	Brown
Shelf Life	6 months when stored at 22°C

Availability

3mm x 12mm x 10m rolls
3mm x 18mm x 10m rolls

All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability of the product for his particular purpose and shall assume all risk and liability in connection therewith. All products are sold subject to Tygavac Advanced Materials standard Conditions of Sale.

TYGAVAC
ADVANCED MATERIALS LTD

Tygavac is a registered trade mark.
2002 - 7 - 2 - 8

VACUUM BAG SEALANT TAPE