



PDA 025

Double sided polyester pressure sensitive adhesive tape

Tygavac Tape PDA 025 is a general purpose double sided tape based on a 25 micron, high tensile, polyester film carrier. The polyester film is coated both sides with an acrylic pressure sensitive adhesive.

The tape is designed to hold items in place in the vacuum bag, bonding well to the majority of our bagging materials.

Typical Properties

| | |
|---|-------------------------------|
| Nominal thickness of polyester film | 0.025mm |
| Overall thickness | 0.080mm |
| Tensile strength | 40 N/cm |
| Elongation at break | 95% |
| Peel adhesion (180°C peel against steel) | 4.0 N/cm |
| Maximum use temperature | 205°C |
| Adhesive | Acrylic |
| Colour | Clear |
| Shelf life | 12 months when stored at 22°C |

Availability

25mm x 33m rolls
Other widths available to special order

+ All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability of the product for his particular purpose and shall assume all risk and liability in connection therewith. All products are sold subject to Tygavac Advanced Materials standard Conditions of Sale.

TYGAVAC
ADVANCED MATERIALS LTD

"Tygavac" is a registered trade mark.
2002 - 7 - 8 - 4