



625C, Vacuum hoses for use 625CC in oven cure applications

Tygavac Hose 625C and 625CC are designed for use in ovens or autoclaves.

They consist of a silicone rubber tube which has an internal spring along the bore to prevent hose collapse. The hose is offered with the choice of external short end spring guards to protect against damage to the hose/end fitting junctions, or a full length external spring guard to prevent damage or kinking.

The hoses are lightweight and highly flexible.

Typical Specifications

Maximum operating temperature	220°C
Tube	Silicone rubber
Inner/outer springs	Galvanised steel
Nominal bore	9.5mm
End fittings	1/4" BSP or 1/4" NPT



Tygavac Hose 625C shown attached to a Tygavac Valve 440TF and Tygavac Connector 440/1



Tygavac Hose 625CC shown attached to a Tygavac Valve 440TF and Tygavac Connector 440

Availability

Tygavac hose 625C	Hose with external short end spring guards
Tygavac Hose 625CC	Hose with full length external spring guard
Standard length available 3m	
Other bores, end fittings and lengths available to special order.	

+ All statements, technical information and recommendations contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability of the product for his particular purpose and shall assume all risk and liability in connection therewith. All products are sold subject to Tygavac Advanced Materials standard Conditions of Sale.

TYGAVAC
ADVANCED MATERIALS LTD

Tygavac is a registered trade mark.
2002 - 7 - 9 - 6